

Apex Engineering Group

Sterlyn Door



Category: Doors, Tubestiles, Turnstiles and Locking Hardware

Sub Category: Building Security Doors

Standard Tested To: MTAS V1.0

Description

The Sterlyn doorset is a 1.8/1.6 Mild Steel fully constructed doors. The door can be inward and outward opening. All outward opening doorsets must have a minimum of 3 No. hinge bolts with a minimum of 19mm engagement. Full gloss finish to RAL colour or primed only The door is hung in a steel frame and has a four sided rebate.

Manufacturer

| | |
|--------------------|-----------------------------------|
| Manufacturer Name: | Apex Engineering Group |
| Country: | N/A |
| Post Code: | SG6 1HJ |
| Address Line 1: | Apex Security Engineering Ltd |
| Address Line 2: | Flint Road Letchworth Garden City |
| State/County: | Hertfordshire |
| Telephone: | +44 (0)1462 673431 |
| Fax: | +44 (0)1462 671518 |
| Website: | N/A |
| Email: | sales@apexsecurityfurniture.com |

Specification

Single leaf dimensions are 750 x 2000 to 1200 x 2300mm (wxh). Double Leaf – 1300 x 2000 to 2000 x 2300mm (wxh).

Total weight (single leaf) excluding locking hardware: 70Kg.

Locking hardware, including mortice locks for key cylinders, have a minimum of 16mm engagement with 20mm bolt throw. External cylinders to have a minimum of LPS 1175 SR2 cylinder guard fitted.