

Heras

Defensor GD 5000 Eliminator

**Category:** Detection Systems**Sub Category:** Barrier Mounted Detection

Description

This system has been assessed over a section of Anti-Intruder Weld Mesh Fence. One loop of sensor cable was attached to the 2nd and 19th strand from the top of the fence fabric using black plastic cable ties every 200 mm with an additional two reinforced metal cable ties per bay. Another run of sensor cable in flexible armoured conduit was tied to the centre strand of the barbed wire topping using plastic cable ties every 200 mm. The installation drawings are held by CPNI.

Manufacturer

Manufacturer Name:	Heras
Country:	N/A
Post Code:	DN4 8WA
Address Line 1:	Hérons Way, Balby
Address Line 2:	Doncaster
State/County:	South Yorkshire
Telephone:	0808 164 2250
Fax:	N/A
Website:	http://www.heras.co.uk
Email:	Sales@heras.co.uk

Specification

The Anti-Intruder Weld Mesh Fence is built to BS 1722 Pt10 and is:

- ? a rolled welded mesh;
- ? apertures of 75 mm vertical x 25 mm horizontal and 3 mm strand thickness;
- ? height of the fence fabric is 2.4 m;
- ? topped with three strands of barbed wire;
- ? overall height of 2.9 m to the top strand of barbed wire; and

? each bay is 3 m in width and buried 300 mm into the ground.

Product Updates

REVISION DATE	COMMENT
01/04/2022	Product discontinued by manufacturer.