

## Bridge deck expansion beam with Populus XA Bollard



Perimeter Barriers | Vehicle

**Manufacturer:** ATG Access

**Standard tested to:** IWA 14-1:2013

**Performance rating:** V/7200[N2A]/48/30:0.2

### Description

Populus XA bollard arrays fitted with an Expansion Barrier Beam.

## Manufacturer

Manufacturer Name:	ATG Access
Country:	N/A
Post Code:	WA11 9TP
Address Line 1:	CoBaCo House, North Florida Road
Address Line 2:	Haydock Industrial Estate
State/County:	Haycock
Telephone:	+44 (0)8456 75 75 74
Fax:	N/A
Website:	<a href="http://www.atgaccess.com">http://www.atgaccess.com</a>
Email:	<a href="mailto:sales@atgaccess.com">sales@atgaccess.com</a>

---

## Specification

The system comprised of two bollard arrays, each with 7 bollards welded onto 4 individual sized and shaped steel plates connected by articable joints within foundations 8802mm long and 1420mm wide.

The expansion joint beam was mounted on the two opposing bollards providing a gap between the bollard mounting plates of 4600mm.

The system was placed on a compacted base 80mm below finished ground level. For the test there was no finished covering, leaving 40mm for either a tarmac or other surface finish.

**Foundation:** B - Depth <= 0.5m below ground level

---